

DYKT2X

防水熱收縮錫環中接管

Insulated Solder Tin Heat Shrink Butt Connector-Water Proof



應用 Application :

專為導線連接,焊錫熱縮保護,防水一次完成設計的產品

One piece design to provide insulation, inspection, strain relief and wire connection. Water resistance



特點 Feature :

- 1.防水絕緣材質 Insulation material with water resistance
- 2.內含熱熔膠具防水功能 With hot melt adhesive inside for waterproof.
- 3.焊錫環設計容易施工 Soldering tin material designed for easy installation.
- 4.具強化接力效果有很好的絕緣保護電子連接器的功能 Reinforced connection for perfectly insulation and protect wires.

工作溫度範圍 temperature range :

- 1.完全收縮溫度 Fully recovery temperature : 150°C
- 2.焊錫開始熔解溫度 Starting temperature of solder melt : 125°C
- 3 操作溫度 Operating temperature : -40°C ~+105°C

材質(Material) : PE



DYKT2X

防水熱縮錫環中接管規格

Insulated Solder tin Heat Shrink Butt Connector-Water Proof Specification

Item NO.	A(內徑 mm)	B(內徑 mm)	L 長度(mm) Length	適用線徑 (AWG/mm ²) Wirre Range	顏色 Color	PCS/BAG
DYKT2X-C-0.5N	3.5±0.3	2.5±0.2	25±2.5	26-22(0.2-0.5)	透明 Transparent	100
DYKT2X-C-1R	5.5±0.3	4.23±0.2	37±2.5	22-16(0.5-1.5)	紅色 Red	100
DYKT2X-C-2U	6.4±0.3	4.7±0.2	37±2.5	16-14(1.5-2.5)	藍色 Blue	100
DYKT2X-C-5Y	8±0.3	6±0.2	42±2.5	12-10(4-6)	黃色 Yellow	100